

# Receiver RV908H32

V1.1  
Jan 2018

## 1. Function



- 1) 12 hub75E interface on board(supports up to 32 scan), no extra hub card needed;
- 2) Single card can output 24 groups RGB data;
- 3) Single card maximum support  $512 \times 512$  pixels (**Please note that there are recommended values depending on the design**)

Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968

of LED screen );

- 4) Support temperature detection;
- 5) Support the cabinet-door monitoring (open/close);
- 6) Two lines fan-speed monitoring;
- 7) Humidity monitoring (humidity sensor sold separately);
- 8) Smoke monitoring (smoke module sold separately);
- 9) Three lines voltage monitoring: one for the system, two for cabinet power;
- 10) Support pixel-by-pixel brightness calibration; single-card color space conversion;
- 11) Support network cable BER test;
- 12) Support hot backup with dual receiver cards for demanding performances screen;
- 13) High refresh rate and high grey level with most of the driver ICs;
- 14) In line with RoHS standards;
- 15) In line with EU standards CE-EMC class B;

## **2.RV908H32 PINOUT**

The receiving card has 2 operating modes, only supporting

Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968

Full-color and two-color screen. Normal mode has 8 available interfaces; 24-group-data-mode has 12 available interfaces. Each interface output data is as following:

R1	1	2	G1
U1	3	4	GND
R2	5	6	G2
U2	7	8	GND
A	9	10	B
C	11	12	D
CLK	13	14	LAT
OE	15	16	GND

### 3.RV908H32 on-board monitoring

Interface on Receiving card(see the silk-screen)	Function	Usage
FAN	2 lines fan speed monitoring	Fan with Control Line
DOOR	cabinet door open/close monitoring	To form Open/close circle
VOLT	voltage monitoring	Connect to VCC
SMOKE	smoke monitoring	Smoke monitoring module SK901 is sold separately
HUM	humidity monitoring	Humidity monitoring module is sold separately
LCD	LCD module for displaying real-time monitoring information	LCD monitoring module is sold separately

### 4.Model table

RV908H32 is in stock. RV918H32 need make to order.

Model	RJ45 Direction	output interface
-------	----------------	------------------

Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968

		type
RV908H	90 Degree	interface in front side
RV918H	180 Degree	interface in front side

## 5. Working conditions

Rated voltage (V)	5	maximum value	5.5	Minimum value	4.5
Rated current (A)	0.80	maximum value	0.87	Minimum value	0.73
Rated power consumption (W)	4.0	maximum value	4.8	Minimum value	3.3
Working temperature (°C)	-20°C ~ 75°C				
Working humidity (%)	0% ~ 95%				

**END**

Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968